



# MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

## MODEL G0555X 14" EXTREME SERIES BANDSAW

### Product Dimensions:

Weight..... 236 lbs.  
Length/Width/Height..... 30 x 26 x 67-1/4 in.  
Foot Print (Length/Width)..... 17-1/4 x 16 in.

### Shipping Dimensions:

#### Carton #1

Type..... Cardboard  
Content..... Machine  
Weight..... 202 Lbs.  
Length/Width/Height..... 44 x 21 x 20 in.

#### Carton #2

Type..... Cardboard  
Content..... Stand  
Weight..... 60 Lbs.  
Length/Width/Height..... 17 x 18 x 26 in.

### Electrical:

Switch..... On/Off Push Button  
Switch Voltage..... 110/220V  
Cord Length..... 6 ft.  
Cord Gauge..... 16 gauge  
Minimum Circuit Size..... 15 amps at 110V, 10 amps at 220V  
Plug Included..... Yes

### Motors:

#### Main

Type..... TEFC Capacitor Start Induction  
Horsepower..... 1-1/2 HP  
Voltage..... 110/220V  
Prewired..... 110V  
Phase..... Single  
Amps..... 15/7.5A  
Speed..... 1725 RPM  
Cycle..... 60 Hz  
Number Of Speeds..... 1  
Power Transfer ..... Belt Drive  
Bearings..... Shielded and Lubricated Ball Bearings

### Main Specifications:

#### Operation

Blade Speeds..... 3000 FPM  
Table Tilt..... Left 10, Right 45 deg.

#### Cutting Capacities

Maximum Cutting Height..... 6 in.  
Max Capacity Left of Blade..... 13-1/2 in.

**Blade Information**

Standard Blade Length..... 93-1/2 in.  
Blade Length Range..... 92-1/2 - 93-1/2 in.  
Blade Width Range..... 1/8 - 3/4 in.  
Upper Blade Guides..... Anti-Collision Ball Bearing  
Lower Blade Guides..... Anti-Collision Ball Bearing  
Guide Post Size.....0.865 in.  
Guide Post Type..... Solid Steel

**Table Information**

Table Length..... 14 in.  
Table Width..... 20-1/2 in.  
Table Thickness..... 1-1/2 in.  
Floor to Table Height..... 44 in.

**Fence Information**

Locks in Front..... Yes  
Locks in Rear..... No  
Adjustable for Blade Lead..... Yes

**Construction**

Table Construction..... Precision Ground Cast Iron  
Rip Fence ..... Extruded Aluminum and Cast Iron  
Base Construction..... Pre-Formed Steel  
Body Construction..... Cast Iron  
Upper Wheel..... Computer Balanced Cast Aluminum  
Lower Wheel..... Computer Balanced Cast Aluminum  
Tire Material..... Rubber  
Wheel Cover ..... Pre-Formed Steel  
Paint..... Powder Coated

**Other Related Information**

Wheel Width..... in. 1-3/16  
Hydraulic Pressure..... in.  
Number of Dust Ports..... 1  
Dust Port Size..... 4 in.  
Mobile Base..... G7314Z

**Other Specifications:**

ISO Factory ..... ISO 9001  
Country Of Origin ..... Taiwan  
Warranty ..... 1 Year  
Serial Number Location ..... Name Label on Top Cover  
Awards ..... Popular Woodworking Best New Tool 2003  
Assembly Time ..... 1-1/2 hours

**Features:**

- Included 6" High Resaw Fence Attachment
- Work Light
- Lower Wheel Brush
- Upper & Lower Ball Bearing Blade Guides
- Deluxe Heavy-Duty Cabinet w/Storage Shelves
- Hinged Wheel Covers
- 4" Dust Port
- 6" Riser Block Available (Model H3051)
- Computer-Balanced Cast-Iron Wheels
- Quick Release Blade Tension
- Included Miter Gauge, Fence, and 3/8" Blade