



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G0656 8" X 72" JOINTER WITH MOBILE BASE

Product Dimensions:

Weight..... 465 lbs.
Length/Width/Height..... 72-1/2 x 26 x 47-1/4 in.
Foot Print (Length/Width)..... 26-3/4 x 16-1/2 in.

Shipping Dimensions:

Carton #1

Type..... Wood Crate
Content..... Machine
Weight..... 390 lbs.
Length/Width/Height..... 25 x 80-3/4 x 14-1/2 in.

Carton #2

Type..... Cardboard
Content..... Stand
Weight..... 132 lbs.
Length/Width/Height..... 18-3/4 x 29-1/4 x 26-5/8 in.

Electrical:

Switch..... ON/OFF Push Button with Large OFF Paddle
Switch Voltage..... 220V
Cord Length..... 6 ft.
Cord Gauge..... 14 guage
Minimum Circuit Size..... 20 amp
Plug Included..... No

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 3 HP
Voltage..... 220V
Prewired..... 220
Phase..... Single
Amps..... 15A
Speed..... 3450 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer V-Belt Drive
Bearings..... Shielded and Lubricated

Main Specifications:

Fence Information

Fence Length..... 35 in.
Fence Width..... 1-1/4 in.
Fence Height..... 5 in.
Fence Stops..... 45, 90 and 135 deg.

Cutting Capacities

| | |
|--------------------------------|----------------------|
| Bevel Jointing..... | Left & Right 45 deg. |
| Maximum Width of Cut..... | 8 in. |
| Maximum Depth of Cut..... | 1/8 in. |
| Maximum Rabbeting Depth..... | 1/2 in. |
| Number of Cuts Per Minute..... | 20000 |

Knife Information

| | |
|-----------------------|-------------|
| Number of Knives..... | 4 |
| Knife Type..... | HSS |
| Knife Length..... | 8 in. |
| Knife Width..... | 3/4 in. |
| Knife Thickness..... | 1/8 in. |
| Knife Adjustment..... | Jack Screws |

Cutterhead Information

| | |
|--------------------------|----------|
| Cutterhead Type..... | 4 Knife |
| Cutterhead Diameter..... | 3 in. |
| Cutterhead Speed..... | 5000 RPM |

Table Information

| | |
|----------------------------|------------|
| Table Length..... | 72-1/2 in. |
| Table Width..... | 9 in. |
| Floor to Table Height..... | 33-1/2 in. |
| Table Adjustment Type..... | Handwheel |

Construction

| | |
|----------------------------------|----------------------------|
| Base Construction..... | Cast Iron |
| Body Assembly Construction..... | Cast Iron |
| Cabinet Construction..... | One-Piece Steel Cabinet |
| Fence Assembly Construction..... | Cast Iron |
| Guard Construction..... | Die Cast Metal |
| Table Construction..... | Precision Ground Cast Iron |
| Dovetailed Ways on Bed..... | Adjustable |
| Parallelogram..... | No |
| Paint..... | Powder Coated |

Other Information

| | |
|---------------------------|-------|
| Number of Dust Ports..... | 1 |
| Dust Port Size..... | 4 in. |

Other Specifications:

| | |
|------------------------------|--------------------------------|
| Country Of Origin | China |
| Warranty | 1 Year |
| Serial Number Location | ID Label on Left Side of Stand |
| Assembly Time | 1 hour |

Features:

- Built-In Easy-to-Use Mobile Base
- Included Push Blocks
- Top Mount Switch Controls
- Handwheel Controlled Fence Adjustment
- Rabbeting Table
- Super Long 72-1/2" Bed