



MACHINE DATA SHEET

Customer Service #: (570) 546-9663 · To Order Call: (800) 523-4777 · Fax #: (800) 438-5901

MODEL G1276 COMBINATION SANDER 6" X 48" BELT 12" DISC 1725 RPM

Product Dimensions:

Weight..... 145 lbs.
Length/Width/Height.....32-1/2 x 16-1/2 x 29-1/2 in.
Foot Print (Length/Width)..... 17 x 14 in.

Shipping Dimensions:

Type..... Cardboard
Content..... Machine
Weight..... 150 lbs.
Length/Width/Height..... 30 x 28 x 18 in.

Electrical:

Switch..... Push Button
Switch Voltage..... 110V
Cord Length..... 5 ft.
Cord Gauge..... 14 gauge
Minimum Circuit Size..... 15 amp
Plug Included..... Yes

Motors:

Main

Type..... TEFC Capacitor Start Induction
Horsepower..... 1 HP
Voltage..... 110/220V
Prewired..... 110V
Phase..... Single
Amps..... 12/6A
Speed..... 1725 RPM
Cycle..... 60 Hz
Number Of Speeds..... 1
Power Transfer Direct Drive
Bearings..... Shielded and Permanently Lubricated

Main Specifications:

Table Info

Table Tilt..... Belt -30 to 45, Disc deg.
Miter Gauge Slot Width..... 3/4 in.
Miter Gauge Slot Height..... 3/8 in.
Belt Table Length..... 12-1/2 in.
Belt Table Width..... 7 in.
Belt Table Thickness..... 1-1/4 in.
Disc Table Length..... 16-1/2 in.
Disc Table Width..... 7 in.
Disc Table Thickness..... 1 in.

Belt Info

Sanding Belt Width.....	6 in.
Sanding Belt Length.....	48 in.
Sanding Belt Speed.....	2500 FPM
Belt Arm Tilt.....	0 - 90 deg.
Height Belt Arm Horizontal.....	14-1/2 in.
Height Belt Arm Vertical.....	29-1/2 in.
Belt Release.....	Quick Release
Drive Roller Type.....	Aluminum
Drive Roller Length.....	6-1/4 in.
Drive Wheel Diameter.....	5 in.
Idler Roller Type.....	Aluminum
Idler Roller Length.....	6-1/4 in.
Idler Roller Diameter.....	3-1/2 in.

Spindle Info

Arbor Size.....	3/4 in.
Total Arbor Length.....	6 in.

Disc Info

Sanding Disc Diameter.....	12 in.
Sanding Disc Speed.....	1725 RPM

Platen Info

Platen Type.....	Cast Iron
Platen Length.....	14-1/2 in.
Platen Width.....	6 in.
Platen Travel.....	1/4 in.

Construction

Base Construction.....	Cast Aluminum
Table Construction.....	Ground Cast Iron
Frame Construction.....	Cast Aluminum
Disc Construction.....	Aluminum
Miter Gauge Construction.....	Die Cast Aluminum/Aluminum Bar
Paint.....	Epoxy

Other

No. Of Dust Ports.....	1
Dust Port Size.....	3 in.

Other Specifications:

ISO Factory	ISO 9001
Country Of Origin	Taiwan
Warranty	1 Year
Serial Number Location	Machine Label on Motor
Assembly Time	45 minutes

Features:

- Belt Table Positive Stops at 90 deg., Disc Table Positive Stops at 45 and 90 deg.
- Quick Belt Release
- Top Roller has Fine Tracking Knob
- Miter Gauge Included
- Two Cast Tables